CITYBAC® 400L



SULO[®]

Citybac® 400L PRODUCT DETAILS









- 1 Flat Lid
- 2 Handle / handle recess
- 3 Handles with handle bar, rear 2x
- 4 Marking areas
- A Body
- **B** DIN comb lifting system, double stage
- **C** Stacking ribs
- **D** Marking areas
- **E** Ergonomic handles lateral 4x
- F Chip nest as standard
- **G** Functional castors 2x
- **H** Swivel castors 2x













STANDARD LID

Dimensions (mm)

A	Height total ~	1165
В	Comb height ~	1070
C	Bin depth ~	775
D	Width total ~	1265

Weights

Volume nominal (L)	400
Empty weight (kg) ~ EN 840 Norm	25
Max. filling weight(kg) ~	160

Dimensions may vary due to production conditions. The specified empty weights are rounded average based on the standard specifications. The actual weight may be different as a result of production conditions and specifications.

Citybac® 400L

PRODUCT DETAILS

COLOURING





Bin bodies made of up to 100 % post-consumption recyclate. We are able to achieve an average share of 70 % domestic recyclate (packaging, caps) and 30 % nondomestic (bins, industrial scrap, pallets)

100% RECYCLED MATERIAL













RAL 7021

RAL 7011

RAL 6011

RAL 6009

RAL 8025

RAL 5023

VIRGIN MATERIAL













RAL 9010

RAL 7038

RAL 5015

RAL 5005

PANTONE 5395C

RAL 3974GN



PANTONE 167 C





RAL 3005



ALTERNATIVE COLOURS FOR THE BIN BODY













+ OPTIONS


FRACTION MARKING



Label for Lid, individual printing possible


LID SLOT SYSTEMS

Packaging




Lid-in-Lid, small Lid always in Yellow

Glass



Round slot with rubber rosette Ø 150 mm, lock or bolt required

Paper



Paper hood for newspapers and magazines in **Blue RAL 5023**

NOISE REDUCTION



Lid closing damper

DRAINAGE



Drain plug

PEDAL



Lid opening via pedal

CHASSIS



Ø 160 mm Wheel-Swivel castor



Ø 160 mm Wheel -Castor with brake



Steering lock (can be fitted to any type of castor)

LOCKING SYTSEMS



Automatic lock with triangular key



Automatic lock with individual key



Manual lock with triangular key

Citybac® 4-Wheel TECHNICAL INFORMATION

	400 LITRE
LIFTING SYSTEM	
DIN COMB	•
LID TYPE	
Standard	•
Domed	
LID SLOT SYSTEMS	
Paper hood	•
Paper hood XXL for cardboards	•
Round slot with rubber rosette Ø 150 mm,	•
Lid-in-Lid,	•
Clip	•
NOISE REDUCTION	
Plots	
Lid Opening Noise Reduction	
LOCKING SYTSEMS	
Manual lock	•
Automatic lock	•
Automatic bolt	
LIFTING DEVICES	
Front	
Swiss	
Trunnions	
Trunnions with metal sleeve	
Forklift device	
Metal trunnions	
CHASSIS	
Standard castors ø 160	•
Standard castors ø 200	
12km/h reinforced wheel ø 160	•
12km/h reinforced wheel ø 200	
Non-marking wheels ø 160	
Non-marking wheels ø 200	

400 LITRE ACCESSOIRES Lid opening via pedal Standard Fixed position with handle at the back of the body Rim reinforcement Bottom reinforcement Towbar **DRAIN PLUG** Drain plug **ANTI-ODOUR** Anti-odour **LABELLING** Photo injection on the lid Standard Sticker Embossing insert Standard Hot foil stamping IDENTIFICATION RFID Chip Specific numbering

sulo.com

